

ODE-3-110043-1012

Optidrive E3 VFD Datasheet

0.75 kW (1 HP), 4.3 A, 110-115 V, 1-3PH

IP20 Variable Frequency Drive



Input Ratings

Supply Voltage	110-115 V
Input Phases	1
Supply Current Continuous	15.8 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	0.75 kW (1 HP)
Output Voltage	0 – 2 x Supply Voltage
Output Current	4.3 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	No Internal Brake Transistor
Enclosure	IP20
Display	LED
PCB Coating	-

Dimensions

Size	1
Height	173 mm (6.81 in)
Width	83 mm (3.27 in)
Depth	123 mm (4.84 in)
Weight	1 kg (2.2 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	165 mm (6.5 in)
Width	125 mm (4.92 in)
Depth	235 mm (9.25 in)
Weight	1.2 kg (2.65 lbs)



Buy this drive or get more information

Find your local sales partner on
inverterkdrives.com



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions



Buy this drive or get more information
Find your local sales partner on
invertekdrives.com

